

Quality Grade PLUS

Bundle Cover : Yes **Bundle Edge Paint** : Non

Cutting:

Different cutting sizes are available upon request and exact MM cut is flexible to meet the demand of different markets considering a width range of 20 to 300 MM, thickness range of 40 to 300 MM and length options of 3 and 4 meters where is, 4 meters is the primary length available.



Specification

Size Tolerance	Net Tally - 2 mm / + 1 mm
Species	SPF (Spruce/Pine/Fir) in various %
Processing	Chamber Dried
Treatment	Kiln Dried (KD)
Moisture Content	18% (+/-2%)
Pith	Allowed
Stain (Blue/Red)	Not Allowed
Resin Pocket	Allowed
Knots	Sound & Dead Knots are Allowed. Loose Knots are not allowed
Wane	Wane Allowed limited to 2 ft of the length. Corner Wanes are Allowed
Mold	Allowed (limited to 10%)
Bark (Hidden/Sunk)	Not Allowed
Insect Hall	Not Allowed
Crack	Shallow Cracks are Allowed
Cutting	Rough No Waves Allowed

Official Notice:

GRADA SPF is made up from living material, thus every piece is unique and no sample piece or photo can act as a reference for all pieces due to several factors such as the age of logs, production season, transit time, potential human error...

Upon choosing GRADA SPF, we assure that we strive to the best of our knowledge and on a daily basis to deliver a consistent quality through our precise grading and selection procedures which confirms to GRADA SPF strict production and quality control standards, however a deviation of certain % from any of the technical details mentioned here in is possible at all times.

Note:
Any allowed characteristic shall not affect the strength of timber